OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION __________TOWNSHIP_ DATE: 8-1-05 PARTY CHIEF: Wilcoxen Banta 6500 S CREW: -TYPE OF MARKER: Harrison Shelby METHOD OF ESTABLISHMENT: County: 2-26-04 IN. S.P.C. E ZONE NAD '83 NAME: 14040704 491225.9623(m) N: 59434.7924(m) E: Banta 6500 S 2. St. Shelby

Original post set 1820 by Hendricks with witness: 24" beech N 72 E 15 links, 30" ash S 38 W 6 links per Marion County Atlas pg. 9. Julian called stone set with witness: 20" tree N 17 W 18 links, 5" beech S 64 E 27 links. Reference 1935 by MCSO called stone. 6-29-75 Fortner called same. 7-2-79 Bruer called rail-road spike over stone. 6-25-87 called same. Excavated 12-10-71 Wilcoxen called (2) railroad spikes fd side by side 1" down. Stone fd 10"x10"x12" down 14". Harrison set. Re-tied 4-17-96. Re-tied 2-11-99 by Wilcoxen. Re-tied 8-1-05 by Wilcoxen. 14040704

REF.	DISTANCE	DESCRIPTION
t	82.49'	Cut 'x' S-end of easterly headwall
ã.	4.3.19	Mag nail w/washer NF PwP#403-758 2"up
3.	76.83	SW concrete wall @ gate to track 24"up
4.	132.00'	Due S to E Q 12-143 Survey mark nail set
5:	85.22'	PK nail F PwP#90-757 6"up
6.	72.00'	Cut 'x' SF concrete light base
7.	51.70'	Road nail F PwP#195-727 10'up